



1	2	3	4	5	6	7	8
REV. DESCRIPTION	DRW. CHK. APP. DATE						
A	RELEASE						

**SPECIFICATIONS**  
 Current Rating: 1 Amp  
 Insulator resistance: 1000 Megohms Min.  
 Contact resistance: 20 m ohms Max.  
 Dielectric withstanding: AC 500V/minute  
 Operating Temperature: -40° ~ +105°C  
 Contact Material: Phosphor Bronze  
 Insulator Material: High Temperature Thermoplastic +Glass Fibre UL94V-0  
 Color: Black  
 Finish: Gold, Tin or Duplex plated  
 Standard: Gold flash all over  
 Duplex plated:  
 Gold plated on contact area  
 Tin on solder area

**Ordering information:**  
 22P8722-XXMXXX-XXX-X  
 Number of Contact: 04~A0(100)  
 10 W/O Locating peg OP with Locating peg  
 Color  
 L LCP  
 G Gold Plated  
 T Tin Plated  
 H Duplex plated  
 Contact Plating  
 01 Normal  
 10 10μ"



**RoHS Compliance**

No. of Contacts		DIMENSIONS	
04	L1	L1	L2
06	1.27	2.94	4.21
08	2.54	4.21	5.48
10	3.81	5.48	6.75
12	5.08	6.75	8.02
14	6.35	8.02	9.29
16	7.62	9.29	10.56
18	8.89	10.56	11.83
20	10.16	11.83	13.10
22	11.43	13.10	14.37
24	12.70	14.37	15.64
26	13.97	15.64	16.91
28	15.24	16.91	18.18
30	16.51	18.18	19.45
32	17.78	19.45	20.72
34	19.05	20.72	21.99
36	20.32	21.99	23.26
38	21.59	23.26	24.53
40	22.86	24.53	25.80
42	24.13	25.80	27.07
44	25.40	27.07	28.34
46	26.67	28.34	29.61
48	27.94	29.61	30.88
50	29.21	30.88	32.15
52	30.48	32.15	33.42
54	31.75	33.42	34.69
56	33.02	34.69	35.96
58	34.29	35.96	37.23
60	35.56	37.23	38.50
62	36.83	38.50	39.77
64	38.10	39.77	41.04
66	39.37	41.04	42.31
68	40.64	42.31	43.58
70	41.91	43.58	44.85
72	43.18	44.85	46.12
74	44.45	46.12	47.39
76	45.72	47.39	48.66
78	46.99	48.66	49.93
80	48.26	49.93	51.20
82	49.53	51.20	52.47
84	50.80	52.47	53.74
86	52.07	53.74	55.01
88	53.34	55.01	56.28
90	54.61	56.28	57.55
92	55.88	57.55	58.82
94	57.15	58.82	60.09
96	58.42	60.09	61.36
98	59.69	61.36	62.63
100	60.96	62.63	63.90

Ref.

成品規格圖		APP.	ANGLES	±3°	SIZE	A4
TITLE 1.27mm Female Header SMT Type		CHK.	LINEAR	0.0	±0.38	SCALE 3:1
PART NO 22P8722-XXMXXX-XXX-X		DR.		0.00±0.25	SHEET 1/1	
UNIT mm(INCH)		PROJECT	KEN		96.01.04	



RECOMMENDED P. C. B. LAYOUT