





REV. DESCRIPTION	DRW. CHK.	CHK. APP.	DATE
A	RELEASE		

**SPECIFICATIONS**  
 Current Rating: 1 Amp  
 Insulator resistance: 1000 Megohms Min.  
 Contact resistance: 25 m ohms Max.  
 Dielectric withstanding: AC 500V/minute  
 Operating Temperature: -40° ~ +105°C  
 Contact Material: Brass  
 Insulator Material: High Temperature Thermoplastic +Glass Fibre UL94V-0  
 Color: Black  
 Finish: Gold, Tin or Duplex plated  
 Standard: Gold flash all over Duplex plated:  
 Gold plated on contact area  
 Tin on solder area

**Ordering information:**  
 22P8262-XXSA6X-XXX-X  
 Number of Contact 04~80  
 Color  
 Contact Plating  
 01 Normal  
 10 10µ"  
 PIN 2  
 PIN 1  
 L1  
 L2  
 2.00  
 2.00



**RoHS Compliance**

ANGLES	±3°	SIZE	A4
LINEAR	0.0 ±0.38	SCALE	3:1
	0.00±0.25	SHEET	1/1
TITLE	2.00mm Female Header Straight Type	CHK.	
PART NO	22P8262-XXSA6X-XXX-X	DR.	KEN
UNIT	mm(INCH)	PROJECT	96.01.04

Dimension mm	L1	L2
2x2	2.00	4.00
2x3	4.00	6.00
2x4	6.00	8.00
2x5	8.00	10.00
2x6	10.00	12.00
2x7	12.00	14.00
2x8	14.00	16.00
2x9	16.00	18.00
2x10	18.00	20.00
2x11	20.00	22.00
2x12	22.00	24.00
2x13	24.00	26.00
2x14	26.00	28.00
2x15	28.00	30.00
2x16	30.00	32.00
2x17	32.00	34.00
2x18	34.00	36.00
2x19	36.00	38.00
2x20	38.00	40.00
2x21	40.00	42.00
2x22	42.00	44.00
2x23	44.00	46.00
2x24	46.00	48.00
2x25	48.00	50.00
2x26	50.00	52.00
2x27	52.00	54.00
2x28	54.00	56.00
2x29	56.00	58.00
2x30	58.00	60.00
2x31	60.00	62.00
2x32	62.00	64.00
2x33	64.00	66.00
2x34	66.00	68.00
2x35	68.00	70.00
2x36	70.00	72.00
2x37	72.00	74.00
2x38	74.00	76.00
2x39	76.00	78.00
2x40	78.00	80.00

Ref.

成品規格圖

RECOMMENDED P. C. B. LAYOUT